

What is claimed is:

- 1 A method for forming a hot melt form for use with an air induction assembly comprising the steps of:
- melting a thermal mastic elastomeric material to a liquid form; and
- 5 applying said liquid elastomeric material to said air induction assembly to create a form.
2. The method as recited in claim 1 further comprising the step blending a gas into said material to form a foamed composition.
3. The method as recited in claim 2 further comprising the step of applying said foamed composition to a base, said foamed composition adhering to said base by a base material consisting of a thermal mastic blend material without a significant amount of gas.
- 10 4. The method as recited in claim 3 further comprising the step of applying a cover to said cured foamed material, said foamed material creating a seal between said base and said cover.
- 15 5. The method as recited in claim 2 wherein said form creates a bumper between said base and a contact point on said air induction assembly.
6. The method as recited in claim 1 wherein the step of applying said elastomeric material further comprises applying said elastomeric material substantially proximate to a cover neck to create a seal and to secure a mass air flow sensor therein.
- 20

FOOT-1294660

- 5

15. A method for forming a hot melt form for use with an air induction assembly comprising the steps of:

melting a thermal mastic elastomeric material to a liquid form; and

applying said elastomeric material substantially proximate to a cover neck of an air

5 induction assembly to create a seal.

16. The method as recited in claim 15 wherein the step of applying said elastomeric material includes dispensing said material into a mold positioned substantially around an interior surface and an exterior surface of said neck.

17. The method as recited in claim 16 further comprising the step of inserting a mass air flow sensor within said neck, said form creating a seal.

18. The method as recited in claim 15 wherein the step of applying said elastomeric material includes dispensing said material through an aperture located in said cover neck, said material dispensing on an interior surface of said neck and an exterior surface of said mass air flow sensor.

15

add
AV
C

0994634-10000